


RCRA20/46-XL-FA106

Radial insert ball bearing

Radial insert ball bearings RCR, with rubber interliner, location by eccentric locking collar, P seals on both sides

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Manufacturing instruction	FA106	Bearing subjected to special noise testing
---------------------------	-------	--

Main Dimensions & Performance Data

d	20 mm	Bore diameter
D	46 mm	Outside diameter
C	18,3 mm	Width, outer ring
B 1	24,5 mm	Locking collar total width
C r	9.400 N	Basic dynamic load rating, radial
C 0r	5.000 N	Basic static load rating, radial
C ur	238 N	Fatigue load limit, radial
	900 N	Load carrying capacity (rubber interliner)
≈m	0,11 kg	Masa

Dimensions

C 2	16 mm	Width outside profile of rubber interliner
S 1	18,6 mm	Distance raceway to locking collar
D 2	35 mm	Flange diameter rubber interliner
d 3	30 mm	Outside diameter locking collar/locknut
P	10 mm	Distance raceway of rubber interliner to face side



Calculation factors

f ₀	13,8	Calculation factor
----------------	------	--------------------

Additional information

	RALE20-XL-NPP-FA106	Bearing designation
Shore A	70 °	Hardness rubber interliner