



IMAGE
COMING SOON




RMEA35-N [↗](#)

Flanged housing unit

Flanged housing unit RMEA...-N

Informacje techniczne



Twoja aktualna wersja produktu

Groove	N	Cast iron housing with undercut slot for end caps
Material	GG	Grey cast iron

Main Dimensions & Performance Data

d	35 mm	Bore diameter
C _r	26.500 N	Basic dynamic load rating, radial
C _{0r}	15.700 N	Basic static load rating, radial
C _{ur}	820 N	Fatigue load limit, radial
≈m	1,15 kg	Masa

Mounting dimensions

J	100 mm	Pitch circle diameter (holes)
N	11,5 mm	Fixing bore
T ₁	9,5 mm	Height spigot
Z	80 mm	Diameter spigot
	h8	Diameter spigot clearance
n	4	Number of screwing holes



Dimensions

A	20,5 mm	Height housing
A ₁	10 mm	Thickness of flange
A ₂	1 mm	Distance raceway
B	34 mm	Width
S	2 mm	Chamfer width
Q	M6	Connection thread for lubrication

Additional information

1	Number of housings
GEHME07-GG-N	Housing
GSH35-XL-2RSR-B	Bearing designation

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.