
**RNA49/32-XL**

Radial roller bearing

Needle roller bearings RNA, to DIN 617/ISO 1206

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Cage	Standard	
Lubrication hole	With	With
Coating	Without	
Type of Seal	Without	
Special features	Without	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

F_w	40 mm	Under roller diameter
D	52 mm	Outside diameter
B	20 mm	Width
C_r	34.500 N	Basic dynamic load rating, radial
C_{0r}	47.500 N	Basic static load rating, radial
C_{ur}	9.100 N	Fatigue load limit, radial
n_G	11.100 1/min	Limiting speed
$n_{G_{Grease}}$	6.700 1/min	Limiting speed for grease lubrication
n_{gr}	6.400 1/min	Reference speed
m	91,37 g	Masa



Dimensions

r _{min}	0,6 mm	Minimum chamfer dimension
C	20 mm	Width, outer ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

G40X52X5	Sealing ring
SD40X52X5	Sealing ring 2

Właściwości

	Obciążenie promieniowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Mala przestrzeń zabudowy