




RNA4902-XL

Radial roller bearing

Needle roller bearings RNA, to DIN 617/ISO 1206

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Cage	Standard	
Lubrication hole	With	With
Coating	Without	
Type of Seal	Without	
Special features	Without	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

F _w	20 mm	Under roller diameter
D	28 mm	Outside diameter
B	13 mm	Width
C _r	12.000 N	Basic dynamic load rating, radial
C _{0r}	13.600 N	Basic static load rating, radial
C _{ur}	2.470 N	Fatigue load limit, radial
n _G	21.100 1/min	Limiting speed
n _G Grease	12.600 1/min	Limiting speed for grease lubrication
n _{gr}	12.000 1/min	Reference speed
m	21,9 g	Masa



Dimensions

r _{min}	0,3 mm	Minimum chamfer dimension
C	13 mm	Width, outer ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

G20X28X4	Sealing ring
SD20X28X4	Sealing ring 2

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Mała przestrzeń zabudowy