


RNA4910-RSR-XL

Radial roller bearing

Needle roller bearings RNA...-RSR, lip seal on one side

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Cage	Standard	
Lubrication hole	the aid of the bearing frequency calculator, you can determine this by inputting the geometrical data.	With
Coating	Without	
Type of Seal	RSR	Contact seal on one side
Special features	Without	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

F _w	58 mm	Under roller diameter
D	72 mm	Outside diameter
C _r	45.000 N	Basic dynamic load rating, radial
C _{0r}	64.000 N	Basic static load rating, radial
C _{ur}	10.800 N	Fatigue load limit, radial
n _G	4.600 1/min	Limiting speed
n _G Grease	4.650 1/min	Limiting speed for grease lubrication
≈m	162,36 g	Masa



Dimensions

r _{min}	0,6 mm	Minimum chamfer dimension
C	22 mm	Width, outer ring

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Uszczelnienie jednostronne
-  Mała przestrzeń zabudowy