

**RNA4916-XL**

Radial roller bearing

Needle roller bearings RNA, to DIN 617/ISO 1206

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Cage	Standard	
Lubrication hole	With	With
Coating	Without	
Type of Seal	Without	
Special features	Without	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

F_w	90 mm	Under roller diameter
D	110 mm	Outside diameter
B	30 mm	Width
C_r	101.000 N	Basic dynamic load rating, radial
C_{0r}	174.000 N	Basic static load rating, radial
C_{ur}	31.000 N	Fatigue load limit, radial
n_G	5.100 1/min	Limiting speed
$n_{G_{Grease}}$	3.050 1/min	Limiting speed for grease lubrication
n_{gr}	3.000 1/min	Reference speed
m	0,515 kg	Masa



Dimensions

r _{min}	1 mm	Minimum chamfer dimension
C	30 mm	Width, outer ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Mała przestrzeń zabudowy