


RNA6906-XL

Radial roller bearing

Needle roller bearings RNA, to DIN 617/ISO 1206

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Cage	Standard	
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Lubrication hole	With	With
Coating	Without	
Lubricant	Without	
Type of Seal	Without	
Special features	Without	
Number of rows	1	Single-row design



Main Dimensions & Performance Data

F _w	35 mm	Under roller diameter
D	47 mm	Outside diameter
B	30 mm	Width
C _r	49.000 N	Basic dynamic load rating, radial
C _{0r}	71.000 N	Basic static load rating, radial
C _{ur}	13.100 N	Fatigue load limit, radial
n _G	12.600 1/min	Limiting speed
n _G Grease	7.500 1/min	Limiting speed for grease lubrication
n _{gr}	6.600 1/min	Reference speed
m	0,126 kg	Masa

Dimensions

r _{min}	0,3 mm	Minimum chamfer dimension
C	30 mm	Width, outer ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Mala przestrzeń zabudowy