




RSHE25-TV-VA-FD

Plummer block housing unit

Plummer block housing units, FD design

Informacje techniczne



Twoja aktualna wersja produktu

Special material	TV	Plastic housing
Corrosion resistant bearing	VA	Corrosion-resistant VA design
Material	TV-FD	Plastic for food industry

Main Dimensions & Performance Data

d	25 mm	Bore diameter
L	76,2 mm	Length
H 2	73,5 mm	Height
≈m	0,35 kg	Masa

Mounting dimensions

J	50,8 mm	Distance fixing bore
K	M10	Thread fixing bore
W	3 mm	Width of flats



Dimensions

H	36,5 mm	Distance shaft axis
A	39,5 mm	Width (base)
B 1	31 mm	Locking collar total width
B 3	35,05 mm	Distance housing centre to cap end
S 1	23,5 mm	Distance raceway to locking collar
Q	1/4"-28 UNF	Connection thread for lubrication
d 3	38,1 mm	Outside diameter eccentric locking collar

Additional information

GEH.SHE05-TV-WHT	Housing
GE25-KRR-B-FA107-VA-FD	Bearing designation
KASK05-S-G-WHT	End cap
KASK05-S-R-NBR-WHT	Open protecting cap

Temperature range

T min	-30 °C	Operating temperature min.
T max	100 °C	Operating temperature max.