



RSHEHY30-VA-FD

Plummer block housing unit

Informacje techniczne

Twoja aktualna wersja produktu

|          |    |                 |
|----------|----|-----------------|
| Material | VA | Stainless Steel |
|----------|----|-----------------|

Main Dimensions & Performance Data

|      |          |                                   |
|------|----------|-----------------------------------|
| d    | 30 mm    | Bore diameter                     |
| L    | 96 mm    | Length total                      |
| H 2  | 93,6 mm  | Height                            |
| U    | 40,2 mm  | Total width unit                  |
| C r  | 16.700 N | Basic dynamic load rating, radial |
| C 0r | 9.110 N  | Basic static load rating, radial  |
| C ur | 760 N    | Fatigue load limit, radial        |
| ≈m   | 1,08 kg  | Masa                              |

Mounting dimensions

|     |            |                      |
|-----|------------|----------------------|
| J   | 76,2 mm    | Distance fixing bore |
| K   | 7/16-14UNC | Thread fixing bore   |
| H 3 | 18 mm      | Thread length        |

Dimensions

|     |         |                                       |
|-----|---------|---------------------------------------|
| H   | 55,6 mm | Distance shaft axis                   |
| A   | 36 mm   | Width (base)                          |
| Y   | 12,7 mm | Distance housing base                 |
| S 1 | 22,2 mm | Distance of raceway to locking collar |



### Additional information

|                   |                     |
|-------------------|---------------------|
| GEH.SHEH06-VA-NAT | Housing             |
| YE30-DC-B-VA-FD   | Bearing designation |
| KASK06-VA-G-NAT   | Protecting cap      |

### Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -20 °C | Operating temperature min. |
| T <sub>max</sub> | 100 °C | Operating temperature max. |