



RSL182206-A-XL

Cylindrical roller bearing

Cylindrical roller bearing RSL18.-XL, full complement roller set, single row, non-locating bearing, no outer ring, 2 ribs on inner ring, type RSL18



X-life

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	30 mm	Bore diameter
E _w	55,19 mm	Outer envelope circle
B	20 mm	Width
C _r	70.000 N	Basic dynamic load rating, radial
C _{0r}	64.000 N	Basic static load rating, radial
C _{ur}	10.400 N	Fatigue load limit, radial
n _G	7.400 1/min	Limiting speed
≈m	187,3 g	Masa

Mounting dimensions

d _{a min}	42 mm	Minimum diameter shaft shoulder
X	14 mm	Raceway width

Dimensions

r _{min}	1 mm	Minimum chamfer dimension
d ₁	42 mm	Maximum rib diameter inner ring
T _K	46,19 mm	Pitch circle



Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia