




RSL182218-A

Cylindrical roller bearing

Cylindrical roller bearing RSL18, full complement roller set, single row, non-locating bearing, no outer ring, 2 ribs on inner ring, type RSL18

Informacje techniczne



Twoja aktualna wersja produktu

Design	A	Internal Variant Cage A
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	90 mm	Bore diameter
E _w	140,61 mm	Outer envelope circle
B	40 mm	Width
C _r	285.000 N	Basic dynamic load rating, radial
C _{0r}	365.000 N	Basic static load rating, radial
C _{ur}	54.000 N	Fatigue load limit, radial
n _G	2.700 1/min	Limiting speed
≈m	1,939 kg	Masa

Mounting dimensions

d _{a min}	110 mm	Minimum diameter shaft shoulder
X	28 mm	Raceway width



Dimensions

r _{min}	2 mm	Minimum chamfer dimension
d ₁	110 mm	Maximum rib diameter inner ring

T _K	121,61 mm	Pitch circle
----------------	-----------	--------------

Temperature range

T _{min}	-30 °C	Operating temperature min.
------------------	--------	----------------------------

T _{max}	120 °C	Operating temperature max.
------------------	--------	----------------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia