



RSL183005-A-XL


Cylindrical roller bearing

Cylindrical roller bearing RSL1830..-XL, full complement roller set, single row, non-locating bearing, no outer ring, 2 ribs on inner ring, type RSL18



X-life

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	25 mm	Bore diameter
E _w	42,51 mm	Outer envelope circle
B	16 mm	Width
C _r	35.000 N	Basic dynamic load rating, radial
C _{0r}	32.000 N	Basic static load rating, radial
C _{ur}	5.600 N	Fatigue load limit, radial
n _G	10.900 1/min	Limiting speed
≈m	80,22 g	Masa

Mounting dimensions

d _{a min}	34,6 mm	Minimum diameter shaft shoulder
X	9 mm	Raceway width

Dimensions

r _{min}	0,6 mm	Minimum chamfer dimension
d ₁	34,6 mm	Maximum rib diameter inner ring
T _K	36,51 mm	Pitch circle



Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Właściwości



Obciążenie promieniowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia