




RSL183026-A

Cylindrical roller bearing

Cylindrical roller bearing RSL1830, full complement roller set, single row, non-locating bearing, no outer ring, 2 ribs on inner ring, type RSL18

Informacje techniczne



Twoja aktualna wersja produktu

Design	A	Internal Variant Cage A
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	130 mm	Bore diameter
E _w	183,81 mm	Outer envelope circle
B	52 mm	Width
C _r	425.000 N	Basic dynamic load rating, radial
C _{0r}	600.000 N	Basic static load rating, radial
C _{ur}	84.000 N	Fatigue load limit, radial
n _G	1.990 1/min	Limiting speed
≈m	3,423 kg	Masa

Mounting dimensions

d _{a min}	149 mm	Minimum diameter shaft shoulder
X	34 mm	Raceway width



Dimensions

r _{min}	2 mm	Minimum chamfer dimension
d ₁	149 mm	Maximum rib diameter inner ring
T _K	157,81 mm	Pitch circle

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia