




RTUE55-XL

Take-up housing unit

Take-up housing units RTUE, cast iron housing, radial insert ball bearing with eccentric locking collar, R seals

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Material	GG	Grey cast iron
----------	----	----------------

Main Dimensions & Performance Data

d	55 mm	Bore diameter
---	-------	---------------

H	145 mm	Height
---	--------	--------

L	169 mm	Length total
---	--------	--------------

B 1	71,4 mm	Locking collar total width
-----	---------	----------------------------

≈m	4,32 kg	Masa
----	---------	------

Mounting dimensions

A 1	22 mm	Width guidance groove
-----	-------	-----------------------

H13		Width guidance groove clearance
-----	--	---------------------------------

H 1	130 mm	Distance guidance grooves
-----	--------	---------------------------

0,15 mm		Upper distance guidance groove tolerance
---------	--	--

-0,15 mm		Lower distance guidance groove tolerance
----------	--	--

N	35 mm	Fixing bore
---	-------	-------------



Dimensions

L 1	104 mm	Distance shaft axis
L 2	17 mm	Length fixed link
L 3	95 mm	Length guidance groove
A	60 mm	Width housing fixing side
N 1	26 mm	Width recess
N 2	63,5 mm	Height recess
S 1	43,6 mm	Distance of raceway to locking collar
T	102 mm	Height housing fixing side
Q	M6	Connection thread for lubrication
A 2	42 mm	Width housing

Additional information

TUE11	Housing
GE55-XL-KRR-B	Bearing designation

Temperature range

T min	-20 °C	Operating temperature min.
T max	120 °C	Operating temperature max.