



RTUEY25-VA-FD

Take-up housing unit

Informacje techniczne

Twoja aktualna wersja produktu

Material	VA	Stainless Steel
----------	----	-----------------

Main Dimensions & Performance Data

d	25 mm	Bore diameter
H	89 mm	Height
L	91,5 mm	Length total
C _{0r}	6.500 N	Basic static load rating, radial
C _{ur}	550 N	Fatigue load limit, radial
C _r	12.200 N	Basic dynamic load rating, radial
≈m	0,87 kg	Masa

Mounting dimensions

A ₁	12 mm	Width guidance groove
H ₁	76 mm	Distance guidance grooves
N	19 mm	Fixing bore



Dimensions

L 1	60 mm	Distance shaft axis
L 2	9 mm	Length fixed link
L 3	44 mm	Length guidance groove
A	32 mm	Width housing fixing side
N 1	18 mm	Width recess
N 2	32 mm	Height recess
B	34,1 mm	Width inner ring
T	46 mm	Height housing fixing side
A 2	25 mm	Width housing

Additional information

GEH.TUE05-VA-NAT	Housing
YE25-DC-B-VA-FD	Bearing designation
KASK05-VA-G-NAT	Protecting cap

Temperature range

T min	-20 °C	Operating temperature min.
T max	100 °C	Operating temperature max.