



RUS19105

Linear recirculating roller bearing unit

Linear roller bearings with spacer elements
RUS..

Informacje techniczne




Twoja aktualna wersja produktu

Size 19105

Main Dimensions & Performance Data

L tot	109 mm	Total length
L	105,5 mm	
B	27 mm	Width
H	19 mm	Height
C	68.000 N	Basic dynamic load rating
C 0	123.000 N	Basic static load rating
≈m	0,29 kg	Masa



Mounting dimensions

L 1	79 mm	Mounting dimension
J B	20,6 mm	Mounting dimension
Tol J B	± 0,1 mm	Tolerance
J L	50 mm	
Tol J L	± 0,1 mm	Tolerance
H 1	0,2 mm	
L 4	85 mm	Minimum support length
L w	10 mm	
H 4	15,2 mm	
T 5	6,2 mm	
G 1	M4	Fixing screws top (DIN ISO 4762-12.9)
G1 M A	5 Nm	Tightening torque fixing screws
K 3	M3	Fixing screws below (DIN ISO 4762-12.9)
K3 M A max	1,8 Nm	Tightening torque fixing screws
D 2	3,5 mm	
	6 mm	

Related products

VUS19105-A	Adjustment gib
UG6628, UGN6628, UZ6628, UZN6628, UFB3210, UFB4710	Suitable Guide rail