



RUS38206

Linear recirculating roller bearing unit

Linear roller bearings with spacer elements
RUS..

Informacje techniczne




Twoja aktualna wersja produktu

Size 38206

Main Dimensions & Performance Data

L _{tot}	206 mm	Total length
L	206,7 mm	
B	52 mm	Width
H	38 mm	Height
C	305.000 N	Basic dynamic load rating
C ₀	550.000 N	Basic static load rating
≈m	2,308 kg	Masa



Mounting dimensions

L 1	158,8 mm	Mounting dimension
J B	41 mm	Mounting dimension
Tol J B	± 0,1 mm	Tolerance
J L	102 mm	
Tol J L	± 0,1 mm	Tolerance
H 1	0,2 mm	
L 4	172 mm	Minimum support length
L W	20 mm	
H 4	31 mm	
T 5	14,2 mm	
G 1	M8	Fixing screws top (DIN ISO 4762-12.9)
G1 M A	41 Nm	Tightening torque fixing screws
K 3	M6	Fixing screws below (DIN ISO 4762-12.9)
K3 M A max	17 Nm	Tightening torque fixing screws
D 2	6,9 mm	
	6 mm	

Related products

VUS38206-A	Adjustment gib
UG12553, UGN12553- A, UZ12553, UZN12553-A, UFG6412, UFB7812	Suitable Guide rail