




RUSV60206-KS

Linear recirculating roller bearing unit

Linear roller bearings, with spacer elements,
with integrated adjusting gib, RUSV...-KS

Informacje techniczne




Twoja aktualna wersja produktu

Size	60206	
Suffix	KS	With end face lubrication connectors

Main Dimensions & Performance Data

L	216 mm	Length total
B	52 mm	Width
H	60 mm	Height
C	305.000 N	Basic dynamic load capacity
C ₀	550.000 N	Basic static load capacity
m	4,15 kg	Masa



Mounting dimensions

L	206 mm	
L ₁	206 mm	
L ₃	158 mm	
L ₄	159 mm	
a	0,3 mm	
L _W	20 mm	
C	10 mm	
E	115 mm	Mounting dimension
F	35 mm	
i	8 mm	Mounting dimension
P ₁	41,5 mm	
d ₁	22 mm	
P ₂	145 mm	
P ₃	18 mm	
d	4 mm	
K	M6	Lubrication connector DIN3405-A
S ₁	8 mm	Hexagon socket adjusting screw
S ₂	4 mm	Hexagon socket counter forcing screw
K	M8	Size thread k DIN
K M _A	41 Nm	Tightening torque fixing screws
D ₂	8,6 mm	
A _{max}	15 mm	Screw stroke A
Delta h _{max}	0,78 mm	Adjustment maximum
	0,05 mm	Adjustment screw revolution



Related products

UG12553,
UGN12553-
A, UZ12553,
UZN12553-A,
UFG6412, UFB7812

Suitable Guide Rails