




FAG

S6302-2RSR>N

Deep groove ball bearing

Deep groove ball bearing S63...-2RSR, corrosion-resistant materials, single row, seals, steel sheet metal cage

Informacje techniczne



Twoja aktualna wersja produktu

Version code	>N	Not marked on bearing
Material Bearing	S	Stainless steel
Type of Seal	2RSR	Contact seal on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Lubricating grease	
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	15 mm	Bore diameter
D	42 mm	Outside diameter
B	13 mm	Width
C _r	12.100 N	Basic dynamic load rating, radial
C _{0r}	5.400 N	Basic static load rating, radial
C _{ur}	335 N	Fatigue load limit, radial
n _G	11.000 1/min	Limiting speed
≈m	81 g	Masa



Mounting dimensions

$d_{a\min}$	20,6 mm	Minimum diameter shaft shoulder
$D_{a\max}$	36,4 mm	Maximum diameter of housing shoulder
$r_{a\max}$	1 mm	Maximum fillet radius

Dimensions

$r_{\min}$	1 mm	Minimum chamfer dimension
D_1	34,7 mm	Shoulder diameter outer ring
D_2	36,6 mm	Caliber diameter outer ring
d_1	24,3 mm	Shoulder diameter inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

Calculation factors

f_0	12,2	Calculation factor
-------	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne
	Ochrona przed korozją