





SK104-207-KTT-B-L402/70 [🔗](#)

Self-aligning deep groove ball bearings

Self-aligning deep groove ball bearings SK...-
KTT-B, Spherical outer ring, inner ring with
hexagonal bore, T seal on both sides

Informacje techniczne



Twoja aktualna wersja produktu

Type of Seal	KTT	Triple lip seals on both sides
Shape of outer surface	B	Spherical
Deviating ballset	207	207

Main Dimensions & Performance Data

D SP	72 mm	Outside diameter
B	37,9 mm	Width
C r	27.500 N	Basic dynamic load rating, radial
C 0r	15.300 N	Basic static load rating, radial
≈m	444 g	Masa



Dimensions

D 1	60 mm	Outside diameter seal
C	19 mm	Width, outer ring
F	37,2 mm	Maximum distance hexagonal bore
r	0,12 mm	Radius hexagonal bore
C 2	22,7 mm	Sealing total width
d 1	46,84 mm	Rib diameter inner ring
d	31,75 mm	Width of flats
	0,15 mm	Width across flats upper tolerance
d	31,75 mm	Width across flats (Inch)
	0,05 mm	Width across flats lower tolerance

Temperature range

T min	-20 °C	Operating temperature min.
T max	100 °C	Operating temperature max.

Calculation factors

f 0	13,8	Calculation factor
-----	------	--------------------

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie dożywotnie, bezobsługowe
	Smarowanie smarem
	Uszczelnienie dwustronne
	Nieosiowość statyczna