



SL045012

Cylindrical roller bearing

Cylindrical roller bearing SL04, full complement roller set, two-row, locating bearing, central rib on outer ring, 3 ribs on inner ring, type SL04

Informacje techniczne

Twoja aktualna wersja produktu

Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	2	Double-row design

Main Dimensions & Performance Data

d	60 mm	Bore diameter
D	95 mm	Outside diameter
B	46 mm	Width
C _r	125.000 N	Basic dynamic load rating, radial
C _{0r}	201.000 N	Basic static load rating, radial
C _{ur}	28.000 N	Fatigue load limit, radial
n _{G Grease}	2.180 1/min	Limiting speed for grease lubrication
m	1,154 kg	Masa



Mounting dimensions

C _{a1}	35 mm	Mounting dim for snap ring WRE (not included in delivery) Tolerance: 0/-0,2
C _{a2}	34 mm	Mounting dim for retaining ring to DIN 471 (not incl. In delivery) Tol: 0/-0,2
d ₁	74 mm	Rib diameter inner ring
d ₂	79 mm	Sealing diameter (rib)
d ₃	104 mm	Outside diameter of snap ring WRE
d _{1 min}	74 mm	Minimum diameter shaft shoulder
	30 °	Chamfer angle
	-0,2 mm	Lower distance snap ring tolerance
	-0,2 mm	Lower distance retaining ring tolerance
	0 mm	Upper distance snap ring tolerance
	0 mm	Upper distance retaining ring tolerance
	0 mm	Lower distance ring groove tolerance
	0,2 mm	Upper distance ring groove tolerance

Dimensions

C	45 mm	Width, outer ring
C ₁	40,2 mm	Distance ring grooves
D ₁	92,4 mm	Diameter of groove
m	3,2 mm	Width of groove
r _{min}	0,6 mm	Minimum chamfer dimension
t	1 mm	Chamfer width
X	36 mm	Distance between rolling elements

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.