




SL181896-E-TB

Cylindrical roller bearing

Cylindrical roller bearing, SL1818...-E-TB
full complement roller set, single row, semi-
locating bearing, 1 rib on outer ring, 2 ribs on
inner ring, type SL18

Informacje techniczne



Twoja aktualna wersja produktu

Design	TB	Bearings with increased axial load capacity
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	480 mm	Bore diameter
D	600 mm	Outside diameter
B	56 mm	Width
C _r	960.000 N	Basic dynamic load rating, radial
C _{0r}	1.970.000 N	Basic static load rating, radial
C _{ur}	195.000 N	Fatigue load limit, radial
n _G	560 1/min	Limiting speed
n _{gr}	365 1/min	Reference speed
m	33,63 kg	Masa



Mounting dimensions

$d_{a \min}$	522 mm	Minimum diameter shaft shoulder
$d_{c \min}$	522 mm	Minimum shaft shoulder
$D_{a \max}$	560 mm	Maximum diameter of housing shoulder
$D_{e \min}$	574,5 mm	Minimum diameter of housing shoulder
$r_{a \max}$	3 mm	Maximum recess radius
E	574,5 mm	Raceway diameter outer ring

Dimensions

$r_{\min}$	3 mm	Minimum chamfer dimension
s	5 mm	Axial displacement
d_1	522 mm	Maximum rib diameter inner ring
$D_1 \min$	560 mm	Minimum rib diameter outer ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Łożysko gabarytowe