


SL182210-XL

Cylindrical roller bearing

Cylindrical roller bearing SL1822...-A-XL, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

X-life

Informacje techniczne





Twoja aktualna wersja produktu

Design	A	Internal Variant A
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	50 mm	Bore diameter
D	90 mm	Outside diameter
B	23 mm	Width
C _r	109.000 N	Basic dynamic load rating, radial
C _{0r}	111.000 N	Basic static load rating, radial
C _{ur}	18.500 N	Fatigue load limit, radial
n _G	5.500 1/min	Limiting speed
n _{gr}	3.000 1/min	Reference speed
≈m	608,2 g	Masa





Mounting dimensions

$d_{a \min}$	64,4 mm	Minimum diameter shaft shoulder
$d_{c \min}$	64 mm	Minimum shaft shoulder
$D_{a \max}$	76,5 mm	Maximum diameter of housing shoulder
$D_{e \min}$	81 mm	Minimum diameter of housing shoulder
$r_{a \max}$	1,1 mm	Maximum recess radius
E	81,4 mm	Raceway diameter outer ring

Dimensions

$r_{\min}$	1,1 mm	Minimum chamfer dimension
s	1 mm	Axial displacement
d_1	64,4 mm	Maximum rib diameter inner ring
$D_1 \min$	76,7 mm	Minimum rib diameter outer ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia