




SL182226

Cylindrical roller bearing

Cylindrical roller bearing SL1822...-A, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

Informacje techniczne



Twoja aktualna wersja produktu

|                           |              |                           |
|---------------------------|--------------|---------------------------|
| Design                    | A            | Internal Variant A        |
| Radial internal clearance | CN (Group N) | Normal internal clearance |
| Tolerance class           | PN           | Normal (ISO 492:2023)     |
| Number of rows            | 1            | Single-row design         |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 130 mm      | Bore diameter                     |
| D               | 230 mm      | Outside diameter                  |
| B               | 64 mm       | Width                             |
| C <sub>r</sub>  | 620.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 850.000 N   | Basic static load rating, radial  |
| C <sub>ur</sub> | 115.000 N   | Fatigue load limit, radial        |
| n <sub>G</sub>  | 1.790 1/min | Limiting speed                    |
| n <sub>gr</sub> | 1.360 1/min | Reference speed                   |
| ≈m              | 10,89 kg    | Masa                              |



Mounting dimensions

|         |           |                                      |
|---------|-----------|--------------------------------------|
| d a min | 162,5 mm  | Minimum diameter shaft shoulder      |
| d c min | 162 mm    | Minimum shaft shoulder               |
| D a max | 197 mm    | Maximum diameter of housing shoulder |
| D e min | 207,5 mm  | Minimum diameter of housing shoulder |
| r a max | 3 mm      | Maximum recess radius                |
| E       | 207,12 mm | Raceway diameter outer ring          |

Dimensions

|         |          |                                 |
|---------|----------|---------------------------------|
| r min   | 3 mm     | Minimum chamfer dimension       |
| s       | 5 mm     | Axial displacement              |
| d 1     | 162,3 mm | Maximum rib diameter inner ring |
| D 1 min | 197 mm   | Minimum rib diameter outer ring |

Temperature range

|       |        |                            |
|-------|--------|----------------------------|
| T min | -30 °C | Operating temperature min. |
| T max | 120 °C | Operating temperature max. |

Właściwości

|                                                                                     |                                   |
|-------------------------------------------------------------------------------------|-----------------------------------|
|  | Obciążenie promieniowe            |
|  | Obciążenie osiowe jednokierunkowe |
|  | Smarowanie smarem                 |
|  | Smarowanie olejem                 |
|  | Bez uszczelnienia                 |