



SL182918-B-XL-C3

Cylindrical roller bearing

Cylindrical roller bearing SL18, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

X-life

Informacje techniczne




Twoja aktualna wersja produktu

Design	B	Internal Variant B
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	90 mm	Bore diameter
D	125 mm	Outside diameter
B	22 mm	Width
C _r	122.000 N	Basic dynamic load rating, radial
C _{0r}	169.000 N	Basic static load rating, radial
C _{ur}	27.000 N	Fatigue load limit, radial
n _G	3.550 1/min	Limiting speed
n _{gr}	2.050 1/min	Reference speed
≈m	0,801 kg	Masa





Mounting dimensions

$d_{a\ min}$	102 mm	Minimum diameter shaft shoulder
$d_{c\ min}$	102 mm	Minimum shaft shoulder
$D_{a\ max}$	110,5 mm	Maximum diameter of housing shoulder
$D_{e\ min}$	115,5 mm	Minimum diameter of housing shoulder
$r_{a\ max}$	1,1 mm	Maximum recess radius
E	115,8 mm	Raceway diameter outer ring

Dimensions

$r_{\min}$	1,1 mm	Minimum chamfer dimension
s	1 mm	Axial displacement
d_1	102 mm	Maximum rib diameter inner ring
$D_1\ min$	110,7 mm	Minimum rib diameter outer ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia