



SL182972-TB-C4

Cylindrical roller bearing

Cylindrical roller bearing SL1829..-TB, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

Informacje techniczne



Twoja aktualna wersja produktu

Design	TB	Bearings with increased axial load capacity
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	360 mm	Bore diameter
D	480 mm	Outside diameter
B	72 mm	Width
C _r	1.280.000 N	Basic dynamic load rating, radial
C _{0r}	2.600.000 N	Basic static load rating, radial
C _{ur}	280.000 N	Fatigue load limit, radial
n _G	730 1/min	Limiting speed
n _{gr}	430 1/min	Reference speed
≈m	37,2 kg	Masa



Mounting dimensions

d a min	399,5 mm	Minimum diameter shaft shoulder
d c min	399,5 mm	Minimum shaft shoulder
D a max	438,5 mm	Maximum diameter of housing shoulder
D e min	450,5 mm	Minimum diameter of housing shoulder
r a max	3 mm	Maximum recess radius
E	450,6 mm	Raceway diameter outer ring

Dimensions

r min	3 mm	Minimum chamfer dimension
s	5 mm	Axial displacement
d 1	399,5 mm	Maximum rib diameter inner ring
D 1 min	438,6 mm	Minimum rib diameter outer ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Łożysko gabarytowe