



SL183022-A

Cylindrical roller bearing

Cylindrical roller bearing SL18...-A, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

Informacje techniczne



Twoja aktualna wersja produktu

Design	A	Internal Variant A
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	110 mm	Bore diameter
D	170 mm	Outside diameter
B	45 mm	Width
C _r	280.000 N	Basic dynamic load rating, radial
C _{0r}	385.000 N	Basic static load rating, radial
C _{ur}	55.000 N	Fatigue load limit, radial
n _G	2.350 1/min	Limiting speed
n _{gr}	2.010 1/min	Reference speed
≈m	3,374 kg	Masa



Mounting dimensions

d a min	127,3 mm	Minimum diameter shaft shoulder
d c min	127 mm	Minimum shaft shoulder
D a max	149 mm	Maximum diameter of housing shoulder
D e min	156,5 mm	Minimum diameter of housing shoulder
r a max	2 mm	Maximum recess radius
E	156,7 mm	Raceway diameter outer ring

Dimensions

r min	2 mm	Minimum chamfer dimension
s	5,5 mm	Axial displacement
d 1	127,3 mm	Maximum rib diameter inner ring
D 1 min	149,3 mm	Minimum rib diameter outer ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia