


SL183028-A-C3

Cylindrical roller bearing

Cylindrical roller bearing SL18...-A, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

Informacje techniczne





Twoja aktualna wersja produktu

Design	A	Internal Variant A
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	140 mm	Bore diameter
D	210 mm	Outside diameter
B	53 mm	Width
C _r	450.000 N	Basic dynamic load rating, radial
C _{0r}	660.000 N	Basic static load rating, radial
C _{ur}	90.000 N	Fatigue load limit, radial
n _G	1.820 1/min	Limiting speed
n _{gr}	1.470 1/min	Reference speed
≈m	5,858 kg	Masa





Mounting dimensions

d a min	162,6 mm	Minimum diameter shaft shoulder
d c min	162 mm	Minimum shaft shoulder
D a max	189,5 mm	Maximum diameter of housing shoulder
D e min	198 mm	Minimum diameter of housing shoulder
r a max	2 mm	Maximum recess radius
E	198,4 mm	Raceway diameter outer ring

Dimensions

r min	2 mm	Minimum chamfer dimension
s	5,5 mm	Axial displacement
d 1	162,2 mm	Maximum rib diameter inner ring
D 1 min	189,5 mm	Minimum rib diameter outer ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia