



**SL185034-A-C3**

Cylindrical roller bearing

Cylindrical roller bearing SL1850...-A, full complement roller set, two-row, semi-locating bearing, 1 rib on outer ring, 3 ribs on inner ring, type SL18

Informacje techniczne



Twoja aktualna wersja produktu

|                           |              |                                   |
|---------------------------|--------------|-----------------------------------|
| Design                    | A            | Internal Variant A                |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN |
| Tolerance class           | PN           | Normal (ISO 492:2023)             |
| Number of rows            | 2            | Double-row design                 |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 170 mm      | Bore diameter                     |
| D               | 260 mm      | Outside diameter                  |
| B               | 122 mm      | Width                             |
| C <sub>r</sub>  | 1.200.000 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 2.110.000 N | Basic static load rating, radial  |
| C <sub>ur</sub> | 270.000 N   | Fatigue load limit, radial        |
| n <sub>G</sub>  | 1.480 1/min | Limiting speed                    |
| n <sub>gr</sub> | 900 1/min   | Reference speed                   |
| ≈m              | 21,8 kg     | Masa                              |



Mounting dimensions

|                     |          |                                      |
|---------------------|----------|--------------------------------------|
| d <sub>c min</sub>  | 198 mm   | Minimum shaft shoulder               |
| d <sub>a min</sub>  | 198,1 mm | Minimum diameter shaft shoulder      |
| D <sub>a max</sub>  | 233 mm   | Maximum diameter of housing shoulder |
| r <sub>a max</sub>  | 2,1 mm   | Maximum recess radius                |
| r <sub>a1 max</sub> | 2,1 mm   | Maximum recess radius                |
| D <sub>e min</sub>  | 232,7 mm | Minimum diameter of housing shoulder |

Dimensions

|                    |          |                                 |
|--------------------|----------|---------------------------------|
| r <sub>min</sub>   | 2,1 mm   | Minimum chamfer dimension       |
| r <sub>1 min</sub> | 2,1 mm   | Minimum chamfer dimension       |
| s                  | 6 mm     | Axial displacement              |
| C                  | 61 mm    | Distance to lubrication hole    |
| d <sub>1</sub>     | 198,1 mm | Maximum rib diameter inner ring |
| D <sub>1 min</sub> | 232,7 mm | Minimum rib diameter outer ring |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 120 °C | Operating temperature max. |

Właściwości

|                                                                                     |                                   |
|-------------------------------------------------------------------------------------|-----------------------------------|
|  | Obciążenie promieniowe            |
|  | Obciążenie osiowe jednokierunkowe |
|  | Smarowanie smarem                 |
|  | Smarowanie olejem                 |
|  | Bez uszczelnienia                 |