




SL192313
Cylindrical roller bearing

Informacje techniczne



Twoja aktualna wersja produktu

Number of rows	1	Single-row design
----------------	---	-------------------

Main Dimensions & Performance Data

d	65 mm	Bore diameter
D	140 mm	Outside diameter
B	48 mm	Width
C _r	310.000 N	Basic dynamic load rating, radial
C _{0r}	345.000 N	Basic static load rating, radial
C _{ur}	55.000 N	Fatigue load limit, radial
n _G	3.200 1/min	Limiting speed
n _{gr}	2.180 1/min	Reference speed
m	3,44 kg	Masa



Dimensions

D_1	116,5 mm	Shoulder diameter outer ring
$D_{a\ max}$	116,5 mm	Maximum diameter of housing shoulder
d_1	90 mm	Shoulder diameter inner ring
$d_{a\ min}$	80,5 mm	Minimum diameter shaft shoulder
$d_{c\ min}$	90 mm	Minimum shaft shoulder
F	80,7 mm	Raceway diameter inner ring
$r_{a\ max}$	2,1 mm	Maximum fillet radius
r_{min}	2,1 mm	Minimum chamfer dimension
s	3,5 mm	Axial displacement

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia