
**SL192330-TB-BR**

Cylindrical roller bearing

Cylindrical roller bearing SL1923, full compl, roller set self-retaining, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type SL19

Informacje techniczne



Twoja aktualna wersja produktu

Number of rows	1	Single-row design
----------------	---	-------------------

Main Dimensions & Performance Data

d	150 mm	Bore diameter
D	320 mm	Outside diameter
B	108 mm	Width
C _r	1.490.000 N	Basic dynamic load rating, radial
C _{0r}	1.900.000 N	Basic static load rating, radial
C _{ur}	235.000 N	Fatigue load limit, radial
n _G	1.350 1/min	Limiting speed
n _{gr}	840 1/min	Reference speed
m	41,8 kg	Masa



Dimensions

D ₁	263,5 mm	Shoulder diameter outer ring
D _{a max}	263,5 mm	Maximum diameter of housing shoulder
d ₁	203,3 mm	Shoulder diameter inner ring
d _{a min}	182 mm	Minimum diameter shaft shoulder
d _{c min}	203 mm	Minimum shaft shoulder
F	182,5 mm	Raceway diameter inner ring
r _{a max}	4 mm	Maximum fillet radius
r _{min}	4 mm	Minimum chamfer dimension
s	7 mm	Axial displacement

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Właściwości

- 

Obciążenie promieniowe
- 

Obciążenie osiowe jednokierunkowe
- 

Smarowanie smarem
- 

Smarowanie olejem
- 

Bez uszczelnienia
- 

Łożysko gabarytowe