




SX011832-A-VSP

Crossed roller bearing

Crossed roller bearingsdimension series 18 to
DIN 616

Informacje techniczne



Twoja aktualna wersja produktu

Preload	VSP	Bearing preload Standard
---------	-----	--------------------------

Main Dimensions & Performance Data

d _i	160 mm	Bore Diameter
	0,004 mm	Bore diameter upper tolerance
	-0,021 mm	Bore diameter lower tolerance
D _a	200 mm	Outside Diameter
	0 mm	Outside diameter upper tolerance
	-0,029 mm	Outside diameter lower tolerance
H	20 mm	Height of the assembled bearing
h _i	20 mm	Height inner ring
	0,1 mm	Width upper tolerance
	-0,1 mm	Width lower tolerance
≈m	1,61 kg	Masa



Dimensions

D _i	180,8 mm	Inner diameter outer ring
D _M	180 mm	Rolling element pitch circle diameter
d _a	179,2 mm	Outer diameter inner ring
h	20 mm	Height of individual ring
	0 mm	Height of individual ring upper tolerance
	-0,025 mm	Height of individual ring lower tolerance
r _{min}	1,1 mm	Chamfer dimension
S	1,5 mm	Diameter of lubrication hole

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	80 °C	Operating temperature max.

Calculation factors

	0,015 mm	Running accuracy, radial
	0,01 mm	Running accuracy, axial
VSP _{min}	0,005 mm	Minimum bearing preload
VSP _{max}	0,02 mm	Maximum bearing preload
C _a	69.000 N	Basic dynamic load rating, axial
C _{0a}	255.000 N	Basic static load rating, axial
C _r	49.000 N	Basic dynamic load rating, radial (for radial load only)
C _{0r}	126.000 N	Basic static load rating, radial (for radial load only)
N _{G oil}	425 1/min	Limiting speed for oil lubrication with preload
N _{G Grease}	210 1/min	Limiting speed for grease lubrication with preload
	61832	Dimensions identical to ISO dimension series 18



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Mała przestrzeń zabudowy