




FAG

T5ED060

Tapered roller bearing

Tapered roller bearings T, main dimensions
acc. to ISO 355, separable

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	PN	Normal (ISO 492:2023)
Heat treatment	Standard	
Cage	Standard	Sheet steel cage, window cage, roller-guided
Quality level	Standard	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	60 mm	Bore diameter
D	115 mm	Outside diameter
B	38 mm	Width, inner ring
C	31 mm	Width, outer ring
T	39 mm	Width, total
C _r	156.000 N	Basic dynamic load rating, radial
C _{0r}	223.000 N	Basic static load rating, radial
C _{ur}	28.500 N	Fatigue load limit, radial
n _G	6.000 1/min	Limiting speed
n _{gr}	4.150 1/min	Thermal speed rating
≈m	1,793 kg	Masa



Mounting dimensions

d _a max	69 mm	Maximum diameter of shaft shoulder
d _b min	76 mm	Minimum diameter of shaft shoulder
D _a min	92 mm	Minimum diameter of housing shoulder
D _a max	105 mm	Maximum diameter of housing shoulder
D _b min	110 mm	Minimum diameter of housing shoulder
C _a min	5,5 mm	Minimum axial space
C _b min	8 mm	Minimum axial space
r _a max	4 mm	Maximum fillet radius of shaft
r _b max	2,5 mm	Maximum fillet radius of housing

Dimensions

r _{1, 2} min	4 mm	Minimum chamfer dimension of inner ring back face
r _{3, 4} min	2,5 mm	Minimum chamfer dimension of outer ring back face
a	33 mm	Distance between the apexes of the pressure cones
d ₁	90,9 mm	Guidance rib diameter of inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Calculation factors

e	0,53	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y	1,13	Dynamic axial load factor
Y ₀	0,62	Static axial load factor

Additional information

T5ED060	Comparative designation to ISO 10317 and ISO 355
---------	--



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia