



FAG


T7FC055-XL-S1

Tapered roller bearing

Tapered roller bearings T, main dimensions
acc. to ISO 355, separable

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	PN	Normal (ISO 492:2023)
Heat treatment	S1	Rings dimensional stabilized up to 200°
Cage	Standard	Sheet steel cage, window cage, roller-guided
Quality level	XL	X-life
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	55 mm	Bore diameter
D	115 mm	Outside diameter
B	31 mm	Width, inner ring
C	23,5 mm	Width, outer ring
T	34 mm	Width, total
C _r	152.000 N	Basic dynamic load rating, radial
C _{0r}	165.000 N	Basic static load rating, radial
C _{ur}	26.000 N	Fatigue load limit, radial
n _G	7.200 1/min	Limiting speed
n _{gr}	5.000 1/min	Thermal speed rating
≈m	1,577 kg	Masa



Mounting dimensions

$d_{a \max}$	65 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	72 mm	Minimum diameter of shaft shoulder
$D_{a \min}$	86 mm	Minimum diameter of housing shoulder
$D_{a \max}$	101 mm	Maximum diameter of housing shoulder
$D_{b \min}$	109 mm	Minimum diameter of housing shoulder
$C_{a \min}$	5 mm	Minimum axial space
$C_{b \min}$	10,5 mm	Minimum axial space
$r_{a \max}$	3 mm	Maximum fillet radius of shaft
$r_{b \max}$	3 mm	Maximum fillet radius of housing

Dimensions

$r_{1, 2 \min}$	3 mm	Minimum chamfer dimension of inner ring back face
$r_{3, 4 \min}$	3 mm	Minimum chamfer dimension of outer ring back face
a	40 mm	Distance between the apexes of the pressure cones
d_1	88,8 mm	Guidance rib diameter of inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

Calculation factors

e	0,87	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y	0,69	Dynamic axial load factor
Y_0	0,38	Static axial load factor

Additional information

T7FC055

Comparative designation to ISO 10317 and ISO 355



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia