




TCJ60-XL-N

Flanged housing unit

Housing units TCJ, four-bolt flanged housing units, cast iron, eccentric locking collar, T seals

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Groove	N	Cast iron housing with undercut slot for end caps
Material	GG	Grey cast iron

Main Dimensions & Performance Data

d	60 mm	Bore diameter
L	175 mm	Flange width
U	80,9 mm	Total height unit
C _r	56.000 N	Basic dynamic load rating, radial
C _{0r}	36.000 N	Basic static load rating, radial
C _{ur}	1.710 N	Fatigue load limit, radial
≈m	4,259 kg	Masa

Mounting dimensions

J	143 mm	Distance fixing bore
N	18 mm	Fixing bore
W	5 mm	Width across flats
n	4	Number of screwing holes



Dimensions

A	47,5 mm	Height housing
A 1	16 mm	Thickness of flange
A 2	34 mm	Distance raceway
B 1	77,9 mm	Locking collar total width
V	150 mm	Shoulder diameter housing
Q	M6	Connection thread for lubrication
d 3	84 mm	Outside diameter locking device

Additional information

1	Number of housings
CJ12	Housing
GE60-XL-KTT-B	Bearing designation
KASK12	Protecting cap

Temperature range

T min	-20 °C	Operating temperature min.
T max	120 °C	Operating temperature max.