

FAG

UCFA206-19

Take-up housing unit

Housing units UCFA, cast iron housing, radial insert ball bearing with grub screws in inner ring, RSR seals, for swivel motion

Informacje techniczne





Twoja aktualna wersja produktu

Material	GG	Grey cast iron

Main Dimensions & Performance Data

d	30,16 mm	Bore diameter
L	144 mm	Length total
U	40,2 mm	Total height unit
≈m	0,9 kg	Masa

Mounting dimensions

N	12 mm	Fixing bore
N_1	58 mm	Length (slot)
N_2	12 mm	Width (slot)
J	117 mm	Distance fixing bore

Dimensions

A_1	14 mm	Thickness of flange
A_2	18 mm	Distance raceway
A	31 mm	Height housing
V	80 mm	Shoulder diameter housing
W	72 mm	Width housing slot side
Q	M6	Connection thread for lubrication

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje

Additional information

	FA206	Housing
	UC206-19	Bearing designation

Temperature range

T_{min}	-20 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje