




FAG

UCFC218

Flanged housing unit

Flanged housing unit UCFC

Informacje techniczne



Twoja aktualna wersja produktu

Material	GG	Grey cast iron
----------	----	----------------

Main Dimensions & Performance Data

d	90 mm	Bore diameter
H	265 mm	Height flange
U	78,3 mm	Total height unit
C _r	102.000 N	Basic dynamic load rating, radial
C _{0r}	72.000 N	Basic static load rating, radial
C _{ur}	3.350 N	Fatigue load limit, radial
≈m	12,21 kg	Masa

Mounting dimensions

J	220 mm	Pitch circle diameter (holes)
N	23 mm	Fixing bore
N ₁	155,55 mm	Distance fixing bore
T ₁	18 mm	Height spigot
Z	190 mm	Diameter spigot
h8		Diameter spigot clearance
n	4	Number of screwing holes



Dimensions

A	50 mm	Height housing
A ₁	20 mm	Thickness of flange
A ₂	22 mm	Distance raceway
B	96 mm	Width
Q	M6	Connection thread for lubrication

Additional information

1	Number of housings
FC218	Housing
UC218	Bearing designation

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.