





FAG

UCP210-32

Plummer block housing unit

Plummer block housing units UCP, cast iron housing, with long base, radial insert ball bearing with grub screws in inner ring, RSR seals

Informacje techniczne



Twoja aktualna wersja produktu

|                   |    |                      |
|-------------------|----|----------------------|
| Material          | GG | Grey cast iron       |
| Housing clearance | J7 | Normal swivel torque |

Main Dimensions & Performance Data

|                 |          |                                   |
|-----------------|----------|-----------------------------------|
| d               | 50,8 mm  | Bore diameter                     |
| L               | 206 mm   | Length total                      |
| H <sub>2</sub>  | 114 mm   | Height                            |
| C <sub>r</sub>  | 37.500 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 23.200 N | Basic static load rating, radial  |
| C <sub>ur</sub> | 1.210 N  | Fatigue load limit, radial        |
| ≈m              | 2,727 kg | Masa                              |

Mounting dimensions

|                |        |                      |
|----------------|--------|----------------------|
| J              | 159 mm | Distance fixing bore |
| N              | 20 mm  | Width (slot)         |
| N <sub>1</sub> | 25 mm  | Length (slot)        |



Dimensions

|                |         |                                       |
|----------------|---------|---------------------------------------|
| H              | 57,2 mm | Distance shaft axis                   |
| A              | 60 mm   | Width (base)                          |
| H <sub>1</sub> | 21 mm   | Height (base)                         |
| B              | 51,6 mm | Width                                 |
| S <sub>1</sub> | 32,6 mm | Distance of raceway to locking collar |
| Q              | M6      | Connection thread for lubrication     |

Additional information

|          |                     |
|----------|---------------------|
| P210     | Housing             |
| UC210-32 | Bearing designation |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -20 °C | Operating temperature min. |
| T <sub>max</sub> | 120 °C | Operating temperature max. |