




FAG

UKT205

Take-up housing unit

Housing units UKT, cast iron housing, radial insert ball bearing with adapter sleeve, RSR seals, for linear motion

Informacje techniczne



Twoja aktualna wersja produktu

Material	GG	Grey cast iron
----------	----	----------------

Main Dimensions & Performance Data

d	20 mm	Bore diameter
---	-------	---------------

H	89 mm	Height
---	-------	--------

L	97 mm	Length total
---	-------	--------------

B 1	35 mm	Locking collar total width
-----	-------	----------------------------

≈m	0,85 kg	Masa
----	---------	------

Mounting dimensions

A 1	12 mm	Width guidance groove
-----	-------	-----------------------

0,2 mm	Upper width guidance groove tolerance
--------	---------------------------------------

0 mm	Lower width guidance groove tolerance
------	---------------------------------------

H 1	76 mm	Distance guidance grooves
-----	-------	---------------------------

0 mm	Upper distance guidance groove tolerance
------	--

-0,5 mm	Lower distance guidance groove tolerance
---------	--

N	19 mm	Fixing bore
---	-------	-------------



Dimensions

L ₁	62 mm	Distance shaft axis
L ₂	10 mm	Length fixed link
L ₃	51 mm	Length guidance groove
A	32 mm	Width housing fixing side
N ₁	16 mm	Width recess
N ₂	32 mm	Height recess
T	51 mm	Height housing fixing side
Q	M6	Connection thread for lubrication
A ₂	24 mm	Width housing

Additional information

T205	Housing
UK205	Bearing designation

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.