


VLU201094-ZT

Slewing ring, 4 point contact bearing, without gear teeth

Slewing ring, 4 point contact bearing, without gear teeth

Informacje techniczne



Twoja aktualna wersja produktu

Centering	ZT	Centering on inner and outer ring
Radial internal clearance	Standard_VL	Standard radial clearance 0 to 0,5 and axial tilting clearance 0 to 0,7

Main Dimensions & Performance Data

d _{iZT}	986 mm	Diameter centring inner ring
	IT8	Diameter centring inner ring tolerance
H	56 mm	Height
D _{aZT}	1.196 mm	Centring diameter outer ring
	-IT8	Diameter centring outer ring tolerance
T	12 mm	Length centering outer ring
t	12 mm	Length centering inner ring
h _a	44,5 mm	Width outer ring
h _i	44,5 mm	Width inner ring
≈m	62,5 kg	Masa



Dimensions

D _i	1.095,5 mm	Inner diameter outer ring
	0,7 mm	Inner diameter outer ring upper tolerance
	0 mm	Inner diameter outer ring lower tolerance
d _a	1.092,5 mm	Outside diameter inner ring
	0 mm	Outside diameter inner ring upper tolerance
	-0,7 mm	Outside diameter inner ring lower tolerance
d _B	18 mm	Fixing bore
L _a	1.170 mm	Pitchcircle diameter fixing holes outer ring
n _a	16	Number of fixing holes in outer ring
L _i	1.012 mm	Pitchcircle diameter fixing holes inner ring
n _i	20	Number of fixing holes in inner ring
F _{r zul}	141.000 N	Max. radial load fixing screws (friction locking)
h _A	20 mm	Ring cross section

Temperature range

T _{min}	-25 °C	Operating temperature min.
T _{max}	80 °C	Operating temperature max.

Calculation factors

C _a	198.000 N	Basic dynamic load rating, axial
C _{0a}	780.000 N	Basic static load rating, axial
C _r	179.000 N	Basic dynamic load rating, radial (for radial load only)
C _{0r}	290.000 N	Basic static load rating, radial (for radial load only)



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Momenty względem wszystkich osi



Smarowanie smarem



Uszczelnienie dwustronne



Łożysko gabarytowe