


XSU140744

Slewing ring, Crossed roller bearing, without gear teeth

Crossed roller bearings, standard series 14,
without gear teeth, lip seals on both sides

Informacje techniczne



Main Dimensions & Performance Data

$d_{i\ ZT}$	674 mm	Diameter centring inner ring
	IT7	Diameter centring inner ring tolerance
t	10 mm	Length centering inner ring
D_a	814 mm	Diameter centring outer ring
	-IT7	Diameter centring outer ring tolerance
T	10 mm	Length centering outer ring
H	56 mm	Height
$\approx m$	51,58 kg	Masa



Dimensions

D _i	745 mm	Inner diameter outer ring
	0,6 mm	Inner diameter outer ring upper tolerance
	0 mm	Inner diameter outer ring lower tolerance
h _a	44,5 mm	Height outer ring
L _a	790 mm	Pitchcircle diameter fixing holes outer ring
n _a	40	Number of fixing holes in outer ring
d _a	743 mm	Outside diameter inner ring
	0 mm	Outside diameter inner ring upper tolerance
	-0,6 mm	Outside diameter inner ring lower tolerance
h _i	44,5 mm	Height of inner ring
d _B	14 mm	Fixing bore
L _i	698 mm	Pitchcircle diameter fixing holes inner ring
n _i	40	Number of fixing holes in inner ring
VSP _{min}	0,01 mm	Min. bearing preload
VSP _{max}	0,04 mm	Maximum bearing preload
	0,05 mm	Running accuracy A (related to the raceway)
	0,05 mm	Running accuracy B (related to the raceway)
	0,09 mm	Running accuracy C (related to the raceway)
	0,08 mm	Running accuracy D (related to the raceway)

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	80 °C	Operating temperature max.



Calculation factors

C_a	275.000 N	Basic dynamic load rating, axial
C_r	195.000 N	Basic dynamic load rating, radial (for radial load only)
C_{0a}	970.000 N	Basic static load rating, axial
C_{0r}	475.000 N	Basic static load rating, radial (for radial load only)
n_G	51 1/min	Limiting speed
$F_{r\text{ zu.}}$	165.200 N	Max. radial load screws

Właściwości

- 

Obciążenie promieniowe
- 

Obciążenie osiowe jednokierunkowe
- 

Obciążenie osiowe dwukierunkowe
- 

Momenty względem wszystkich osi
- 

Smarowanie smarem
- 

Uszczelnienie dwustronne
- 

Łożysko gabarytowe