


XV110

Crossed roller bearing

Crossed roller bearings without gear teeth,
lamellar seals on both sides

Informacje techniczne



Main Dimensions & Performance Data

d _i	110 mm	Bore Diameter
	0,016 mm	Bore diameter upper tolerance
	-0,006 mm	Bore diameter lower tolerance
D _a	180 mm	Outside Diameter
	0 mm	Outside diameter upper tolerance
	-0,025 mm	Outside diameter lower tolerance
h _i	23 mm	Height inner ring
≈m	2,283 kg	Masa

Dimensions

D _i	127,5 mm	Inner diameter outer ring
d _a	126,5 mm	Outer diameter inner ring
H _a	22 mm	Width outer ring
L _a	160 mm	Pitch circle diameter fixing holes
n _B	16	Quantity of fixed holes evenly around the circumference
d _B	9 mm	Diameter fixing hole outer ring
d _S	15 mm	Countersunk diameter of fixing holes
t _S	8,5 mm	Countersunk depth of fixing holes



Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	80 °C	Operating temperature max.

Calculation factors

	0,01 mm	Running accuracy, radial
	0,01 mm	Running accuracy, axial
C _a	57.000 N	Basic dynamic load rating, axial
C _{0a}	180.000 N	Basic static load rating, axial
C _r	40.500 N	Basic dynamic load rating, radial (for radial load only)
C _{0r}	88.000 N	Basic static load rating, radial (for radial load only)
F _{r zul.}	28.200 N	Max. radial load screws (frictional contact)
N _G Grease	602 1/min	Limiting speed for grease lubrication with normal clearance
N _G Grease	301 1/min	Limiting speed for grease lubrication with preload

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Momenty względem wszystkich osi
	Smarowanie smarem
	Uszczelnienie dwustronne
	Mala przestrzeń zabudowy