



25.08.2026, 10:44:52 UTC


SCHAEFFLER

YRTCM180-XL

Axial/radial roller bearing

Axial/radial bearings, double direction, screw mounting, with integrated angular measuring system

Informacje techniczne



Twoja aktualna wersja produktu

Angular measuring system integrated	M	With incremental angular measuring system
-------------------------------------	---	---

Main Dimensions & Performance Data

d	180 mm	Bore diameter
	0 mm	Bore diameter upper tolerance
	-0,013 mm	Bore diameter lower tolerance
D	280 mm	Outside diameter
	0 mm	Outside diameter upper tolerance
	-0,018 mm	Outside diameter lower tolerance
H	44 mm	Height
C _r	100.000 N	Basic dynamic load rating, radial
C _{0r}	200.000 N	Basic static load rating, radial
C _a	134.000 N	Basic dynamic load rating, axial
C _{0a}	730.000 N	Basic static load rating, axial
n _G	600 1/min	Limiting speed
M _R	5 Nm	Bearing friction torque at 5 1/min
≈m	7,351 kg	Masa

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje



Mounting dimensions

J	194 mm	Pitch circle diameter fixing holes in inner ring
J 1	260 mm	Pitch circle diameter fixing holes in outer ring
d 1	7 mm	Fixing holes diameter inner ring
d 2	11 mm	Counterbore diameter of fixing holes
a	6,2 mm	Counterbore depth of fixing holes
	46	Quantity of fixing holes inner ring
d 3	7 mm	Fixing holes diameter outer ring
	45	Quantity of fixing holes outer ring
n	48	Pitch quantity
t	7,5 °	Pitch separation angle
G	M8	Threaded extraction hole
	3	Quantity of threaded extraction hole
M A	14 Nm	Screw tightening torque
	2	Quantity of retaining screws

t 1 4 µm Axial and radial runout, measurement standard; Measured on mounted bearing, with ideal adjacent construction.

Dimensions

H 1	30 mm	Height contact face outer ring
	0,03 mm	Height contact face outerring H1 upper tolerance
	-0,03 mm	Height contact face outerring H1 lower tolerance
H 2	14 mm	Height contact face outer ring
	0,025 mm	Height contact face outerring H2 upper tolerance
	-0,025 mm	Height contact face outerring H2 lower tolerance
H M	10 mm	Height shaft washer
D 1 max	245,1 mm	Maximum diameter inner ring
D M	244,38 mm	Diameter of dimensional scale on shaft locating washer
C	15 mm	Width of outer ring



Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

c _{aL}	9.400 N/μm	Axial rigidity of bearing position
c _{rL}	5.000 N/μm	Radial rigidity of bearing position
c _{kL}	46.000 Nm/mrad	Tilting rigidity of bearing position
c _{aW}	13.500 N/μm	Axial rigidity of rolling element set
c _{rW}	5.300 N/μm	Radial rigidity of rolling element set
c _{kW}	88.500 Nm/mrad	Tilting rigidity of rolling element set

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Momenty względem wszystkich osi
-  Smarowanie smarem
-  Bez uszczelnienia