






ZARF1560-L-TV

Needle roller/axial cylindrical roller bearing

Needle roller/axial cylindrical roller bearings
ZARF..-L, double direction, for screw
mounting, long shaft locating washer

Informacje techniczne




Twoja aktualna wersja produktu

Cage	TV	Plastic Cage made from PA66
Locating Feature , bearing outer ring	L	Stepped shaft locating washer extended on one side

Main Dimensions & Performance Data

d	15 mm	Bore diameter
D	60 mm	Outside diameter
H	53 mm	Hight
C _a	24.900 N	Basic dynamic load rating, axial
C _{0a}	53.000 N	Basic static load rating, axial
C _r	13.000 N	Basic dynamic load rating, radial
C _{0r}	17.500 N	Basic static load rating, radial
C _{ua}	7.500 N	Fatigue load limit, axial
C _{ur}	2.650 N	Fatigue load limit, radial
n _{G Oil}	8.500 1/min	Limiting speed for oil lubrication
n _{G Grease}	2.200 1/min	Limiting speed for grease lubrication
M _{RL}	0,35 Nm	Bearing friction torque
≈m	405,6 g	Masa



Mounting dimensions

D a max	36 mm	Maximum diameter of housing shoulder
d a min	22 mm	Minimum diameter shaft shoulder
t 1	0,1 mm	Position bore in the housing

Dimensions

H 1	39 mm	Height outer ring over wave washer
C	14 mm	Width, outer ring
C 1	8 mm	Distance to lubrication hole
D 1	35 mm	Rip diameter shaft washer
D 2	24 mm	Heeldiameter wave washer long
D 3	34 mm	Outside diameter wave washer long
B	7,5 mm	Width, wave washer
B 1	20,5 mm	Width wave washer long
B 2	11 mm	Width heel wave washer long
r min	0,3 mm	Minimum chamfer dimension
r 1 min	0,6 mm	Minimum chamfer dimension
d 1	3,2 mm	Diameter lubrication hole
J	46 mm	Pitch circle diameter (holes)
n	6	Number of screwing holes
n x t	60 °	Splīt

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.



Additional information

c_{aL}	1.400 N/ μ m	Rigidity axial
c_{kL}	110 Nm/mrad	Tilting stiffness
M_m	0,274 kg*cm2	Mass moment of inertia
	1 μ m	Axial runout
radial	ZMA15/33	Recommended INA precision locknut for radial locking (not included)
axial	AM15	Locknut 2
M_A	10 Nm	Tightening torque nut
	6.506 N	Preload force axial
	24X35X7	Sealing ring
	M6	Screw size
n_a	6	Number of screws
na x ta	60 °	Division (screwing holes)

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia