






ZARF1762-L-TV

Needle roller/axial cylindrical roller bearing

Needle roller/axial cylindrical roller bearings
ZARF..-L, double direction, for screw
mounting, long shaft locating washer

Informacje techniczne




Twoja aktualna wersja produktu

Cage	TV	Plastic Cage made from PA66
Locating Feature , bearing outer ring	L	Stepped shaft locating washer extended on one side

Main Dimensions & Performance Data

d	17 mm	Bore diameter
D	62 mm	Outside diameter
H	57 mm	Hight
C a	26.000 N	Basic dynamic load rating, axial
C 0a	57.000 N	Basic static load rating, axial
C r	14.000 N	Basic dynamic load rating, radial
C 0r	19.900 N	Basic static load rating, radial
C ua	8.000 N	Fatigue load limit, axial
C ur	3.000 N	Fatigue load limit, radial
n G Oil	7.800 1/min	Limiting speed for oil lubrication
n G Grease	2.100 1/min	Limiting speed for grease lubrication
M RL	0,4 Nm	Bearing friction torque
≈m	0,458 kg	Masa



Mounting dimensions

D a max	39 mm	Maximum diameter of housing shoulder
d a min	26 mm	Minimum diameter shaft shoulder
t 1	0,1 mm	Position bore in the housing

Dimensions

H 1	41,5 mm	Height outer ring over wave washer
C	14 mm	Width, outer ring
C 1	8 mm	Distance to lubrication hole
D 1	38 mm	Rip diameter shaft washer
D 2	28 mm	Heeldiameter wave washer long
D 3	38 mm	Outside diameter wave washer long
B	9 mm	Width, wave washer
B 1	23 mm	Width wave washer long
B 2	11 mm	Width heel wave washer long
r min	0,3 mm	Minimum chamfer dimension
r 1 min	0,6 mm	Minimum chamfer dimension
d 1	3,2 mm	Diameter lubrication hole
J	48 mm	Pitch circle diameter (holes)
n	6	Number of screwing holes
n x t	60 °	Splīt

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.



Additional information

c _{aL}	1.600 N/μm	Rigidity axial
c _{kL}	160 Nm/mrad	Tilting stiffness
M _m	0,464 kg*cm2	Mass moment of inertia
	1 μm	Axial runout
radial	ZM17	Recommended INA precision locknut for radial locking (not included)
axial	AM17	Locknut 2
M _A	12 Nm	Tightening torque nut
	7.078 N	Preload force axial
	28X40X7	Sealing ring
	M6	Screw size
n _a	6	Number of screws
na x ta	60 °	Division (screwing holes)

Właściwości

- 

Obciążenie promieniowe
- 

Obciążenie osiowe jednokierunkowe
- 

Obciążenie osiowe dwukierunkowe
- 

Smarowanie smarem
- 

Smarowanie olejem
- 

Bez uszczelnienia