


**ZARN45105-L-TV**

Needle roller/axial cylindrical roller bearing

Needle roller/axial cylindrical roller bearings
ZARN...-L, double direction, long shaft
locating washer

Informacje techniczne



Twoja aktualna wersja produktu

Cage	TV	Plastic Cage made from PA66
Locating Feature , bearing outer ring	L	Stepped shaft locating washer extended on one side

Main Dimensions & Performance Data

d	45 mm	Bore diameter
D	105 mm	Outside diameter
H	103 mm	Hight
C _a	154.000 N	Basic dynamic load rating, axial
C _{0a}	405.000 N	Basic static load rating, axial
C _r	40.000 N	Basic dynamic load rating, radial
C _{0r}	82.000 N	Basic static load rating, radial
C _{ua}	37.500 N	Fatigue load limit, axial
C _{ur}	11.500 N	Fatigue load limit, radial
n _{G Oil}	3.300 1/min	Limiting speed for oil lubrication
n _{G Grease}	1.150 1/min	Limiting speed for grease lubrication
M _{RL}	3,5 Nm	Bearing friction torque
≈m	3,407 kg	Masa

Mounting dimensions

D _{a max}	91 mm	Maximum diameter of housing shoulder
d _{a min}	68 mm	Minimum diameter shaft shoulder



Dimensions

H ₁	74,5 mm	Height outer ring over wave washer
C	25 mm	Width, outer ring
D ₁	90 mm	Rip diameter shaft washer
D ₂	70 mm	Heeldiameter wave washer long
D ₃	88 mm	Outside diameter wave washer long
B	17,5 mm	Width, inner ring
B ₁	38,5 mm	Width wave washer long
B ₂	18 mm	Width heel wave washer long
r _{min}	0,3 mm	Minimum chamfer dimension
r _{1 min}	0,6 mm	Minimum chamfer dimension

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

c _{aL}	4.000 N/μm	Rigidity axial
c _{kL}	2.100 Nm/mrad	Tilting stiffness
M _m	28,1 kg*cm ²	Mass moment of inertia
	1 μm	Axial runout
radial	ZMA45/85	Recommended INA precision locknut for radial locking (not included)
axial	AM45	Recommended INA precision locknut for axial locking (not included)
M _A	150 Nm	Tightening torque nut
	33.549 N	Required locknut force
	70X90X10	Rotary shaft seal to DIN 3760 (not included)



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia