





ZKLF1762-2Z-XL

Axial angular contact ball bearing

Axial angular contact ball bearings ZKLF..-2Z, double direction, for screw mounting, gap seals on both sides

X-life

Informacje techniczne




Twoja aktualna wersja produktu

Type of Seal	2Z	Minimal gap seal on both sides
Tolerance class	Standard	

Main Dimensions & Performance Data

d	17 mm	Bore diameter
	0 mm	Bore diameter upper tolerance
	-0,005 mm	Bore diameter lower tolerance
D	62 mm	Outside diameter
	0 mm	Outside diameter upper tolerance
	-0,01 mm	Outside diameter lower tolerance
B	25 mm	Width
	0 mm	Width upper tolerance
	-0,25 mm	Width lower tolerance
C _a	20.800 N	Basic dynamic load rating, axial
C _{0a}	31.500 N	Basic static load rating, axial
C _{ua}	1.920 N	Fatigue load limit, axial
n _G Grease	10.100 1/min	Limiting speed for grease lubrication
n _g	6.600 1/min	Thermally safe operating speed
M _R	0,12 Nm	Bearing frictional torque
≈m	0,457 kg	Masa



Mounting dimensions

D _a max	37 mm	Maximum diameter of housing
d _a min	23 mm	Minimum diameter shaft
t ₁	0,1 mm	Position tolerance of bore in the housing
	M6	Size of fixing screws
n _a	3	Number of holes in adjacent construction
t _a	120 °	Pitch separation angle of holes in adjacent construction

M6 Connection thread for lubrication

Dimensions

d ₁	30 mm	Rib diameter inner ring
r _{min}	0,3 mm	Minimum chamfer dimension
r _{1 min}	0,6 mm	Minimum chamfer dimension
J	48 mm	Pitch circle diameter fixing holes
d ₂	6,8 mm	Fixing holes diameter
b	3 mm	Width of extraction slot
l	17 mm	Distance of extraction slot
n	6	Pitch quantity of fixing holes
t	60 °	Pitch separation angle of fixing holes
a	60 °	Contact angle

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.



Additional information

c_{aL}	450 N/ μ m	Rigidity axial
c_{kL}	80 Nm/mrad	Tilting rigidity
M_m	0,132 kg*cm2	Mass moment of inertia
	2 μ m	Axial runout
	ZM17	Recommended INA precision locknut for radial locking
	AM17	Recommended INA precision locknut for axial locking
M_A	15 Nm	Tightening torque for the recommended INA precision locknut
	7.514 N	Required locknut force axial

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne