




ZKLFA0850-2RS

Axial angular contact ball bearing

Angular contact ball bearing units
ZKLFA...-2RS, double direction, for screw
mounting, lip seals on both sides, with
flattened flange

Informacje techniczne




Twoja aktualna wersja produktu

Type of Seal	2RS	Contact lip seal on both sides
--------------	-----	--------------------------------

Main Dimensions & Performance Data

d	8 mm	Bore diameter
	0 mm	Bore diameter upper tolerance
	-0,005 mm	Bore diameter lower tolerance
D	32 mm	Outside diameter
	0 mm	Outside diameter upper tolerance
	-0,01 mm	Outside diameter lower tolerance
B	20 mm	Width
	0 mm	Width upper tolerance
	-0,25 mm	Width lower tolerance
C _a	12.500 N	Basic dynamic load rating, axial
C _{0a}	16.300 N	Basic static load rating, axial
C _{ua}	740 N	Fatigue load limit, axial
n _G Grease	12.100 1/min	Limiting speed for grease lubrication
n _g	5.100 1/min	Thermally permissible speed
≈m	0,131 kg	Masa



Mounting dimensions

d _{a min}	11 mm	Minimum diameter shaft shoulder
d _{a max}	25 mm	Maximum diameter of shaft shoulder
t ₁	0,1 mm	Position tolerance
	M5	Screw size

n _a	4	Number of screws
----------------	---	------------------

Dimensions

d ₁	19 mm	Rib diameter inner ring
r _{min}	0,3 mm	Minimum chamfer dimension
r _{1 min}	0,6 mm	Minimum chamfer dimension
B ₁	8 mm	Thickness of flange
d ₂	5,5 mm	Fixing boring diameter
J	40 mm	Pitch circle diameter (holes)
A	35 mm	Flange width

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

M _{RL}	0,08 Nm	Bearing friction torque
c _{aL}	250 N/μm	Rigidity axial
c _{kL}	20 Nm/mrad	Tilting stiffness
M _m	0,02 kg*cm2	Mass moment of inertia
	2 μm	Axial runout
	ZM08	Recommended INA precision locknut for radial locking (not included)
M _A	4 Nm	Tightening torque nut
	3.468 N	Locknut force axial



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne