


**ZKLN1034-2RS-XL**

Axial angular contact ball bearing

Axial angular contact ball bearing  
ZKLN...-2RS-XL, double direction, no screw  
mounting

X-life

## Informacje techniczne



## Twoja aktualna wersja produktu

|                 |          |                                 |
|-----------------|----------|---------------------------------|
| Type of Seal    | 2RS      | Contact lip seals on both sides |
| Tolerance class | Standard |                                 |

## Main Dimensions &amp; Performance Data

|                          |              |                                       |
|--------------------------|--------------|---------------------------------------|
| d                        | 10 mm        | Bore diameter                         |
|                          | 0 mm         | Bore diameter upper tolerance         |
|                          | -0,005 mm    | Bore diameter lower tolerance         |
| D                        | 34 mm        | Outside diameter                      |
|                          | 0 mm         | Outside diameter upper tolerance      |
|                          | -0,01 mm     | Outside diameter lower tolerance      |
| B                        | 20 mm        | Width                                 |
|                          | 0 mm         | Width upper tolerance                 |
|                          | -0,25 mm     | Width lower tolerance                 |
| C <sub>a</sub>           | 14.700 N     | Basic dynamic load rating, axial      |
| C <sub>0a</sub>          | 18.800 N     | Basic static load rating, axial       |
| C <sub>ua</sub>          | 1.140 N      | Fatigue load limit, axial             |
| n <sub>G</sub><br>Grease | 10.900 1/min | Limiting speed for grease lubrication |
| n <sub>g</sub>           | 4.600 1/min  | Thermally safe operating speed        |
| M <sub>R</sub>           | 0,12 Nm      | Bearing frictional torque             |
| ≈m                       | 0,097 kg     | Masa                                  |



Mounting dimensions

|         |       |                             |
|---------|-------|-----------------------------|
| D a max | 28 mm | Maximum diameter of housing |
| d a min | 14 mm | Minimum diameter shaft      |

Dimensions

|         |        |                           |
|---------|--------|---------------------------|
| d 1     | 21 mm  | Rib diameter inner ring   |
| r min   | 0,3 mm | Minimum chamfer dimension |
| r 1 min | 0,6 mm | Minimum chamfer dimension |
| α       | 60 °   | Contact angle             |

Temperature range

|       |        |                            |
|-------|--------|----------------------------|
| T min | -30 °C | Operating temperature min. |
| T max | 120 °C | Operating temperature max. |

Additional information

|      |              |                                                             |
|------|--------------|-------------------------------------------------------------|
| c aL | 325 N/μm     | Rigidity axial                                              |
| c kL | 25 Nm/mrad   | Tilting rigidity                                            |
| M m  | 0,029 kg*cm2 | Mass moment of inertia                                      |
|      | 2 μm         | Axial runout                                                |
|      | ZM10         | Recommended INA precision locknut for radial locking        |
| M A  | 6 Nm         | Tightening torque for the recommended INA precision locknut |
|      | 4.891 N      | Required locknut force axial                                |



### Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne