


ZKLN3062-2Z-2AP-XL

Axial angular contact ball bearing

Axial angular contact ball bearings
ZKLN...-2Z-2AP-XL, matched pair, double
direction, gap seals on both sides



X-life

Informacje techniczne



Twoja aktualna wersja produktu

Type of Seal	2Z	Minimal gap seal on both sides
Tolerance class	Standard	
Number of bearings	2AP	Axial angular contact ball bearings, matched pair



Main Dimensions & Performance Data

d	30 mm	Bore diameter
	0 mm	Bore diameter upper tolerance
	-0,005 mm	Bore diameter lower tolerance
D	62 mm	Outside diameter
	0 mm	Outside diameter upper tolerance
	-0,01 mm	Outside diameter lower tolerance
B	56 mm	Width
	0 mm	Width upper tolerance
	-0,5 mm	Width lower tolerance
C _a	52.000 N	Basic dynamic load rating, axial
C _{0a}	127.000 N	Basic static load rating, axial
C _{ua}	7.700 N	Fatigue load limit, axial
n _G Grease	6.700 1/min	Limiting speed for grease lubrication
n _g	4.300 1/min	Thermally safe operating speed
M _R	0,5 Nm	Bearing frictional torque
≈m	0,801 kg	Masa

Mounting dimensions

D _{a max}	53 mm	Maximum diameter of housing
d _{a min}	40 mm	Minimum diameter shaft

Dimensions

d ₁	45,5 mm	Rib diameter inner ring
r _{min}	0,3 mm	Minimum chamfer dimension
r _{1 min}	0,6 mm	Minimum chamfer dimension
α	60 °	Contact angle



Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Additional information

c _{aL}	1.500 N/μm	Rigidity axial
c _{kL}	620 Nm/mrad	Tilting rigidity
M _m	1,46 kg*cm2	Mass moment of inertia
	2,5 μm	Axial runout
	ZMA30/52	Recommended INA precision locknut for radial locking
	AM30	Recommended INA precision locknut for axial locking
M _A	32 Nm	Tightening torque for the recommended INA precision locknut
	9.947 N	Required locknut force axial

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne